


SCREWED BRONZE "Y" STRAINERS – 250YTB Series



Model 250YTB



RATINGS

PMO (maximum operating pressure): 250 psi @ 406°F
400 psi @ 150°F

NOTES

- **SCREENS:** 20 Mesh type 304SS supplied as standard. Other meshes, perforations and materials are available upon request
- **CAPS:** Straight threaded and gasketed caps with a plugged blowdown connection are standard on all sizes.
- Also available with sweat type end connections – Model 250YSB (Dimension "A" will differ from below, contact factory)

MATERIALS

PART	DESCRIPTION
Body	B62 – Cast Bronze
Screen	304 Stainless Steel
Gasket	Silicone
Cap	B62 – Cast Bronze
Plug	B62 – Cast Bronze

DIMENSIONS AND WEIGHTS

Size		DIMENSIONS						Weight	
		A		B		C			
mm	in	mm	in	mm	in	mm	in	kg	lbs
15	1/2	78	3-1/16	57	2-1/4	10	3/8	0.57	1-1/4
20	3/4	90	3-17/32	64	2-1/2	10	3/8	0.68	1-1/2
25	1	106	4-1/8	81	3-1/8	20	3/4	0.91	2
32	1-1/4	129	5-1/16	92	3-5/8	20	3/4	1.36	3
40	1-1/2	151	5-15/16	106	4-1/8	20	3/4	1.81	4
50	2	197	7-3/4	146	5-3/4	20	3/4	3.4	7-1/2

Colton has a policy of continuous product research and improvement and reserves the right to change design and specifications without notice



Tel: 1-888-300-9155 Fax: 1-888-300-9160 www.COLTONIND.com info@coltonind.com